

SAFETY DATA

PRODUCT NAME: **KF-131,132,133 (White, Colors & Clear)**

Page 1 of 6

SPR INTERNATIONAL INC.
320 Northpoint Pkwy. Suite L
Acworth, Ga. 30102

02-03-2012

OFFICE TELEPHONE NUMBER: Acworth, Ga. (770) 966-1331

EMERGENCY TELEPHONE NUMBER: 3-E 1-800-451-8346, Office 8:00am to 5:00pm Mon-Fri
E.S. Time 1-800-346-7882

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: * TRADEMARK **Polysilicone** KF-131, 132, 133

SPR * SUPER HIGH SOLID Polyurethane Enamel, Non-Lead Colors
PRODUCT NUMBERS AND COLORS

This MSDS covers products with MSDS code SPR, GLAZE HIGH SOLID including: Black , Blue, Red, Orange, Yellow, Hi-Gloss White, Lo-gloss White & Clear Glaze.

--- also Lead Hazard Free Polyurethane Glaze * HS Custom Colors ---

PRODUCT CLASS

Base component for 2-package Poly Glaze Coating

SECTION II -- HAZARDOUS INGREDIENTS

CAS NO. INGREDIEN % by WEIGHT ACGIH-TLV OSHA-PEL UNITS V.P.

108-88-3	<< Toluene.	0-5	100	100	PPM	22.0
		STEL	150	150	PPM	
1330-20-7	<< Xylene.	0-5	100	100	PPM	5.9
		STEL	150	150	PPM	
78-93-3	< Methyl Ethyl Ketone.	1-10	200	200	PPM	70.0
		STEL	300	300	PPM	
108-94-1	Cyclohexanone	0-10	25	25	(Skin) PPM	2.0
108-21-4	Isopropyl Acetate.	5-15	250	250	PPM	47.5
123-86-4	n-Butyl Acetate.	STEL	310	310	PPM	
		STEL	150	150	PPM	10.0
14807-96-6	Talc	0-20	2	2	Mg/M3 as Resp. Dust	
13463-67-7	Titanium Dioxide	0-45	10	10(5)	Mg/M3 as Dust ***	
1333-86-4	Carbon Black	<5	3.5	3.5	Mg/M3 as Dust	

[in Blacks only] ***Total Dust (Respirable Fraction)

<<These ingredients are subject to the reporting requirements of Section 313,
(Title III Superfund Amendments and Reauthorization Act) and 40 CFR Part 372.

SAFETY DATA

PRODUCT NAME: **KF-131,132,133 (White, Colors & Clear)**

Page 2 of 6

SPR INTERNATIONAL INC.
320 Northpoint Pkwy. Suite L
Acworth, Ga. 30102

OFFICE TELEPHONE NUMBER: Acworth, Ga. (770) 966-1331

EMERGENCY TELEPHONE NUMBER: 3-E 1-800-451-8346, Office 8:00am to 5:00pm Mon-Fri
E.S. Time 1-800-346-7882

SECTION II -- PHYSICAL DATA

PRODUCT WEIGHT -- 8.0-12.6 lb./gal.	EVAPORATION RATE -- Slower than Ether
SPECIFIC GRAVITY -- 0.96-1.51	VAPOR DENSITY -- Heavier than Air
BOILING RANGE -- 174-320 F	MELTING POINT -- N.A.
VOLATILE VOLUME -- 22-42 %	SOLUBILITY IN WATER -- N.A.

SECTION IV -- FIRE AND EXPLOSION HAZARD

FLAMMABILITY CLASSIFICATION FLASH POINT 25-51 F PMCC LEL 1.0 UEL 7.0

RED LABEL -- Flammable, Flash below 100 F

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when used to extreme heat.

SECTION V -- HEALTH HAZARD DATA

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

SAFETY DATA

PRODUCT NAME: **KF-131,132,133 (White, Colors & Clear)**

Page 3 of 6

SPR INTERNATIONAL INC.
320 Northpoint Pkwy. Suite L
Acworth, Ga. 30102

OFFICE TELEPHONE NUMBER: Acworth, Ga. (770) 966-1331

EMERGENCY TELEPHONE NUMBER:3-E 1-800-451-8346, Office 8:00am to 5:00pm Mon-Fri
E.S. Time 1-800-346-7882

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

May cause allergic respiratory and/or skin reaction in susceptible persons or sensitization. This effect may be delayed several hours after exposure.

EMERGENCY AND FIRST AID PROCEDURES

IF INHALED: If any breathing problems occur during use, **LEAVE THE AREA** and get fresh air. If problems remain or occur later, **IMMEDIATELY** get medical attention.

IF on SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and laundry before re-use.

IF in EYES: Flush eyes with large amounts of water for about 15 minutes. Get medical attention.

IF SWALLOWED: Get medical attention.

CHRONIC Health Hazards

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Methyl Ethyl Ketone may increase the nervous system effects of other solvents.

Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary, blood forming, cardio-vascular, and reproductive systems.

Persons sensitive to isocyanates will experience increased allergic reaction on repeated exposure.

Rats exposed to titanium dioxide dust at 250mg./m³ developed lung cancer, however, such exposure levels are not attainable in the workplace.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

SAFETY DATA

PRODUCT NAME: **KF-131,132,133 (White, Colors & Clear)**

Page 4 of 6

SPR INTERNATIONAL INC.
320 Northpoint Pkwy. Suite L
Acworth, Ga. 30102

OFFICE TELEPHONE NUMBER: Acworth, Ga. (770) 966-1331

EMERGENCY TELEPHONE NUMBER: 3-E 1-800-451-8346, Office 8:00am to 5:00pm Mon-Fri
E.S. Time 1-800-346-7882

SECTION VI -- REACTIVITY DATA

STABILITY -- STABLE

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION -- WILL NOT OCCUR

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

SECTION VIII - PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE

NO PERSON SHOULD USE THIS PRODUCT, OR BE IN THE AREA WHERE IT IS BEING USED, IF THEY HAVE CHRONIC (LONG-TERM) LUNG OR BREATHING PROBLEMS OR IF THEY EVER HAD A REACTION TO ISOCYANATES.

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin

SAFETY DATA

PRODUCT NAME: **KF-131,132,133 (White, Colors & Clear)**

Page 5 of 6

SPR INTERNATIONAL INC.
320 Northpoint Pkwy. Suite L
Acworth, Ga. 30102

OFFICE TELEPHONE NUMBER: Acworth, Ga. (770) 966-1331

EMERGENCY TELEPHONE NUMBER: 3-E 1-800-451-8346, Office 8:00am to 5:00pm Mon-Fri
E.S. Time 1-800-346-7882

and eyes. Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may present at hazardous levels only during sanding or abrading of the dried film.

If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m³ (total dust), OSHA PEL 15 mg./me (total dust), 5mg./m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

Where overspray is present, a positive pressure air supplied respirator (TC19C NIOSH/MSHA approved) should be worn. If unavailable, a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II may be effective. Follow respirator manufacturer's directions for use. Wear the respirator for the whole time of spraying and until all vapors and mists are gone. **NO PERSONS SHOULD BE ALLOWED IN THE AREA WHERE THIS PRODUCT IS BEING USED UNLESS EQUIPPED WITH THE RESPIRATOR PROTECTION RECOMMENDED FOR THE PAINTERS.**

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section II.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PROTECTIVE EQUIPMENT

Use barrier cream on exposed skin.

SAFETY DATA

PRODUCT NAME: **KF-131,132,133 (White, Colors & Clear)**

Page 6 of 6

SPR INTERNATIONAL INC.
320 Northpoint Pkwy. Suite L
Acworth, Ga. 30102

OFFICE TELEPHONE NUMBER: Acworth, Ga. (770) 966-1331

EMERGENCY TELEPHONE NUMBER: 3-E 1-800-451-8346, Office 8:00am to 5:00pm Mon-Fri
E.S. Time 1-800-346-7882

SECTION IX - PRECAUTIONS

DOL STORAGE CATEGORY -- 1B

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Contents are **FLAMMABLE**. Keep away from heat sparks, and open flame. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

OTHER PRECAUTIONS

This product must be mixed with other components before use. Before opening the packages, **READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.**

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

HEALTH	3
FLAMMABILITY	2
REACTIVITY	0

This Material Safety Data Sheet conforms to the Hazard Communication standard, 29 CFR 1910.1200(g)(4), for similar complex mixtures.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.