

MATERIAL SAFETY DATA SHEET

Page 1 of 3

PRODUCT NAME: Slip-Grip "Green" Slip Resistant Coating
PRODUCT CODE: Slip-Grip "Green" Part A & B

PRODUCT CODE: Slip-Grip "Green" A/B-XX MATERIAL SAFETY DATA SHEET

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURED FOR: SPR International Inc.

ADDRESS: 320 Northpoint PKWY Suite L
Acworth, GA 30102

EMERGENCY PHONE: 3E 1-800-451-8346

INFORMATION PHONE: (770) 966-1331

EFFECTIVE DATE: **02/08/2012**

NAME OF PREPARER: Larry Stevens

SECTION II - HAZARDOUS INGREDIENTS SARA III INFORMATION

HAZARDOUS COMPONENTS	VAPOR PRESSURE CAS NUMBER	WEIGHT mm HG @ TEMP	PERCENT
Diacetone Alcohol OSHA PEL 50ppm, ACGIH 50ppm, Niosh 50ppm		< 1MM@20° C	< 1

*** NO TOXIC CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372.

NO INFORMATION AVAILABLE.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: ESTIMATED 212 F SPECIFIC GRAVITY (H2O=1): 1.28

VAPOR DENSITY: LIGHTER THAN AIREVAPORATION RATE: SLOWER THAN ETHER

COATING V.O.C.: 1.26 LB/GL

SOLUBILITY IN WATER: SOLUBLE

APPEARANCE AND ODOR: OPAQUE COATING, SWEET SMELL

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A

METHOD USED: CLOSED CUP

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

USE FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS TO PROTECT FIREFIGHTERS FROM HAZARDOUS COMBUSTION PRODUCTS. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT EXPLOSION OF LIDS FROM PRESSURE BUILD-UP.

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE DUE TO BUILD UP OF STEAM WHEN EXPOSED TO EXTREME HEAT.

SECTION V - REACTIVITY DATA

STABILITY: STABLE
CONDITIONS TO AVOID N/A

INCOMPATIBILITY (MATERIALS TO AVOID): AVOID STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: POSSIBLE OXIDES OF CARBON AND NITROGEN

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INHALATION OF VAPOR OR MIST CAN CAUSE THE FOLLOW: HEADACHE; NAUSEA; IRRITATION OF NOSE, THROAT AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

DIRECT CONTACT WITH MATERIAL MAY CAUSE THE FOLLOWING: SLIGHT IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE THE FOLLOWING: SLIGHT SKIN IRRITATION.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

WHILE THIS MATERIAL HAS A LOW DEGREE OF TOXICITY, INGESTION OF EXCESSIVE QUANTITIES MAY CAUSE IRRITATION OF THE DIGESTIVE TRACT.

HEALTH HAZARDS (ACUTE AND CHRONIC)

INGESTION AND SKIN ABSORPTION: NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION. INHALATION: MAY BE IRRITATING TO MUCOUS MEMBRANES, RESPIRATORY TRACT, AND MAY PRODUCE SYMPTOMS OF HEADACHE OR NAUSEA IN POORLY VENTILATED AREAS. PROLONGED SKIN CONTACT MAY CAUSE REDDENING OF THE SKIN. DIRECT EYE CONTACT MAY CAUSE EYE IRRITATION.

CARCINOGENICITY: NTP: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

THIS MATERIAL HAS NOT BEEN IDENTIFIED AS A CARCINOGEN BY NTP, IARC OR OSHA.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

PRE-EXISTING LUNG CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO THIS MATERIAL.

EMERGENCY AND FIRST AID PROCEDURES

SWALLOWING: NO HARMFUL EFFECTS EXPECTED. INHALATION: NO EMERGENCY CARE ANTICIPATED. EYES AND SKIN: IMMEDIATELY FLUSH EYES WITH WATER UNTIL WATER IS NO LONGER CLOUDY. WASH SKIN WITH SOAP AND WATER UNTIL WATER IS NO LONGER CLOUDY. IF CLOTHING IS SOAKED, REMOVE AND WASH BEFORE REUSE. TOXICOLOGY STUDIES OF SIMILAR MATERIALS HAVE SHOWN VERY LOW ACUTE TOXICITY. THERE IS NO SPECIFIC ANTIDOTE. TREATMENT OF OVER EXPOSURE SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITION.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

RESTRICT AREA TO ONLY THOSE PERSONNEL NEEDED. MAJOR SPILLS SHOULD BE COLLECTED FOR DISPOSAL. MINOR SPILLS MAY BE FLUSHED INTO SEWER IF PERMITTED BY STATE, FEDERAL AND LOCAL REGULATIONS.

WASTE DISPOSAL METHOD

INCINERATE OR BURY IN SUITABLE LANDFILL WHERE PERMITTED BY APPROPRIATE GOVERNMENT REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP CONTAINERS COOL AND DRY. USE AND STORE THIS PRODUCT WITH ADEQUATE VENTILATION. KEEP PRODUCT CONTAINERS CLOSED WHEN NOT IN USE. AVOID SUBJECTING THIS PRODUCT TO EXTREME TEMPERATURE VARIATIONS AND FREEZING.

OTHER PRECAUTIONS

DO NOT STORE BELOW 40 DEGREES FAHRENHEIT.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION

RESPIRATORY PROTECTION MAY BE NECESSARY TO MINIMIZE EXPOSURE TO VAPORS DEPENDING ON THE NATURE AND CONCENTRATION OF THE AIRBORNE MATERIAL. USE A RESPIRATOR WITH APPROPRIATE FILTERS AND CARTRIDGES (NIOSH APPROVED) OR SUPPLIED AIR EQUIPMENT.

VENTILATION

IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE TO MINIMIZE EXPOSURE, ADDITIONAL VENTILATION OR EXHAUST SYSTEMS MAY BE REQUIRED.

PROTECTIVE GLOVES

USE GLOVES MADE OF NEOPRENE, BUTYL RUBBER OR NATURAL RUBBER.

EYE PROTECTION

USE CHEMICAL SPLASH GOGGLES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

IT IS SUGGESTED THAT A SOURCE OF CLEAN WATER BE AVAILABLE IN THE WORK AREA FOR FLUSHING EYES AND SKIN. IMPERVIOUS CLOTHING SHOULD BE WORN AS NEEDED.

WORK/HYGIENIC PRACTICES

AFTER USING THIS PRODUCT WASH HANDS THOROUGHLY PRIOR TO EATING OR SMOKING.

SECTION IX - DISCLAIMER

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH SPR INTERNATIONAL INC. OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE AND SUITABLE TO THEIR CIRCUMSTANCES. TO OUR KNOWLEDGE, THIS MSDS COMPLIES WITH 29 CFR 1910, 1200.